

### Features

- Multifunction handshower offers wide coverage and concentrated spray settings.
- Ergonomic design is comfortable and easy to grip.
- MasterClean™ sprayface is easy to clean.
- 2.5 gpm (gallons per minute) flow rate.
- KOHLER finishes resist corrosion and tarnishing.

### Installation

- Bracket or slidebar required for wall-mount installation.
- Deck-mount holder required for deck-mount installation.

### Required Products/Accessories

K-8593 72" Shower Hose  
K-9660 Vacuum Breaker

or

K-9514 60" Shower Hose  
K-9660 Vacuum Breaker

or

K-45981 72" ribbon hose  
K-9660 Vacuum Breaker

or

K-45982 60" ribbon hose  
K-9660 Vacuum Breaker



OBC

### Codes/Standards

ASME A112.18.1/CSA B125.1  
DOE - Energy Policy Act 1992  
OBC


### KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	2BZ	Oil-Rubbed Bronze
	BL	Matte Black



### Technical Information

All product dimensions are nominal.

#### Handshower:

Rated maximum flow: 2.5 gal/min (9.5 l/min)

Pressure: 80 psi (5.5 bar)

### Notes

Install this product according to the installation guide.

Plumbing codes require an atmospheric vacuum breaker (such as Kohler Model K-9660) be installed in-line with handshowers. Please consult with local plumbing officials.

NOTE: Handshower contains flow regulating check valve for backflow prevention.

OBC compliant when installed to the specific requirements of these regulations.